

New generation of battery powered plastic strapping tools for mobile strapping applications

This new, most versatile plastic strapping tool is a further development of the famous and well established P320 and P321 models. The new tool is very user-friendly and suitable for most applications in all industrial sectors. Tensioning as well as sealing cycles are activated by pressing a lever with the thumb.



Characteristics

Strapping qualities:	Polypropylene (PP) and Polyester (PET)	
Strapping dimensions:	widths	12.7 – 19.0 mm / 1/2 – 3/4"
	thicknesses	0.40 – 1.35 mm / .025 - .053"
Weight:	4.5 kg / 9.9 lbs	
Dimension:	L335 x W165 x H135 mm	
Average seal strength:	up to 80% (dependent on strap quality)	
Strap tension:	650 – 3000 N (adjustable)	
Tensioning speed:	152 – 225 mm/s	
Power supply:	Battery	14.4VDC / 2.4 Ah NiCD
	Battery	14.4VDC / 2.7 Ah NiMH
Suspension bracket (optional)		

Advantages

- Simple one-handed operation
- Strap tensioning and welding time adjustment
- Easy strap threading; Both straps are inserted together
- Quick battery exchange

Chart of types model P323

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.3101	P323/12.7/0.65-1.05	12.7	1/2	0.65-1.05	.025-.041	3000	675	152-225	6-8.9
43.3111	P323/13/0.65-1.05	13		0.65-1.05	.025-.041	3000	675	152-225	6-8.9
43.3121	P323/16/0.65-1.05	16	5/8	0.65-1.05	.025-.041	3000	675	152-225	6-8.9
43.3122	P323/16/1.06-1.35	16	5/8	1.06-1.35	.042-.053	3000	675	152-225	6-8.9
43.3131	P323/19/0.40-0.64	19	3/4	0.40-0.64	.016-.025	3000	675	152-225	6-8.9
43.3132	P323/19/0.65-1.05	19	3/4	0.65-1.05	.025-.041	3000	675	152-225	6-8.9
43.3133	P323/19/1.06-1.35	19	3/4	1.06-1.35	.042-.053	3000	675	152-225	6-8.9

Battery chargers for model P323

Item No.	Model	Charging type	Tension	Countries
N5.4414	Battery standard charger	NiCd & NiMH	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, EY, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, Z, ZA, ZW
N5.4422	Battery turbo charger	NiCd & NiMH	220-240 V / 50-60 Hz	(same as N5.4414)
N5.4416	Battery standard charger	NiCd & NiMH	240 V / 50-60 Hz	BRN, BRU, CY, EAK, EAT, GB, IRL, M, MAL, OM, SGP, Y
N5.4428	Battery turbo charger	NiCd & NiMH	240 V / 50-60 Hz	(same as N5.4416)
N5.4426	Battery turbo charger	NiCd & NiMH	110 V / 50 Hz	GB
N5.4418	Battery standard charger	NiCd & NiMH	230-240 V / 50-60 Hz	AUS, NZ
N5.4430	Battery turbo charger	NiCd & NiMH	230-240 V / 50-60 Hz	(same as N5.4418)
N5.4424	Battery turbo charger	NiCd & NiMH	110-127 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4420	Battery standard charger	NiCd & NiMH	220 V / 60 Hz	ROK
N5.4407	Battery mobile charger	NiCd only	-	all countries

Replacement battery for model P323

Item No.	Model	Tension	Power
N5.4309	Accu NiCd P322 / P323	14.4VDC	2.4 Ah
N5.4316	Accu NiMH P322 / P323	14.4VDC	2.7 Ah

Accessories

19.9420 Tool promotional case for P322 / P323