

Battery powered plastic strapping tools – the new generation



Characteristics

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths	16.0 – 19.0 mm / 5/8 – 3/4"
	thicknesses	0.40 – 1.35 mm / .016 - .053"
Weight:		4.4 kg / 9.7 lbs
Dimension:		L355 x W128 x H128 mm
Average seal strength:		up to 75% (dependent on strap quality)
Strap tension:		600 – 3500 N (adjustable)
Tensioning speed:		100 – 130 mm/s
Power supply:	Battery	14.4VDC / 2.4 Ah NiCD
	Battery	14.4VDC / 2.7 Ah NiMH
Suspension bracket (optional)		

Advantages

- Ergonomic design with small handle
- Well balanced and very light tool good for all strapping positions
- Simple one-handed operation
- Very high tension force with adjustable tension speed
- Tension force and sealing time adjustable
- Easy strap threading; Both straps are inserted together
- Welding lever locks in bottom position and allows the preparation of the next strapping during welding and cooling
- Tools welds without tension (strap repair)
- Quick battery exchange

Chart of types model P325

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.0721	P325/16/0.65-1.05	16	5/8	0.65-1.05	.025-.041	3500	787	100-130	3.9-5
43.0722	P325/16/1.06-1.35	16	5/8	1.06-1.35	.042-.053	3500	787	100-130	3.9-5
43.0731	P325/19/0.40-0.64	19	3/4	0.40-0.64	.016-.025	3500	787	100-130	3.9-5
43.0732	P325/19/0.65-1.05	19	3/4	0.65-1.05	.025-.041	3500	787	100-130	3.9-5
43.0733	P325/19/1.06-1.35	19	3/4	1.06-1.35	.042-.053	3500	787	100-130	3.9-5

Battery chargers for model P325

Item No.	Model	Charging type	Tension	Countries
N5.4414	Battery standard charger	NiCd & NiMH	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, EY, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, Z, ZA, ZW
N5.4422	Battery turbo charger	NiCd & NiMH	220-240 V / 50-60 Hz	(same as N5.4414)
N5.4416	Battery standard charger	NiCd & NiMH	240 V / 50-60 Hz	BRN, BRU, CY, EAK, EAT, GB, IRL, M, MAL, OM, SGP, Y
N5.4428	Battery turbo charger	NiCd & NiMH	240 V / 50-60 Hz	(same as N5.4416)
N5.4426	Battery turbo charger	NiCd & NiMH	110 V / 50 Hz	GB
N5.4418	Battery standard charger	NiCd & NiMH	230-240 V / 50-60 Hz	AUS, NZ
N5.4430	Battery turbo charger	NiCd & NiMH	230-240 V / 50-60 Hz	(same as N5.4418)
N5.4424	Battery turbo charger	NiCd & NiMH	110-127 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4420	Battery standard charger	NiCd & NiMH	220 V / 60 Hz	ROK
N5.4407	Battery mobile charger	NiCd only	-	all countries

Replacement battery for model P325

Item No.	Model	Tension	Power
N5.4309	Accu NiCd P322 / P323	14.4VDC	2.4 Ah
N5.4316	Accu NiMH P322 / P323	14.4VDC	3.0 Ah

Accessories

P32.0112	Standard suspension bracket
P32.0137	Suspension bracket for alternating positions
P32.0127	Wearing plate for rough surfaces
P32.1129	Turning button kit